



returning id of data type to identify data type

Search

Advanced Search  
Preferences

Web Show options... Results 61 - 70 of about 17,000,000 for **returning id of data type to identify data type**. (0.13 seconds)

1. DATEVALUE function returning "Data Type Mismatch" only when ...

Jan 14, 2009 ... If I sort, I get the error "**Data Type Mismatch**." As long as I don't sort, I don't get an error. How do I modify this formula to **return** a ...

www.experts-exchange.com/Programming/Languages/SQL\_Syntax/Q\_24052984.html  
- 53k - [Cached](#) - [Similar pages](#)

2. BEGIN LICENSE BLOCK \*\*\*\*\* Version: MPL 1.1/GPL 2.0/LGPL 2.1 ...

toArray(new **Datatype**[0])); **return** ds; } /\*\* \* Gets a set of datatypes that is superclasses, in this set, to a given datatypes \* @param **id** identifies the ...  
fisheye1.allassian.com/browse/~raw,r=1.8/scam/scamController/src/se/kmr/scam/client/**datatype**/impl/**DatatypeSetImpl**.java - 15k - [Cached](#) - [Similar pages](#)

3. Original **data types** in Active Record query result? | CodeIgniter ...

7 posts - 2 authors - Last post: Apr 2  
but it also returns my **ID** columns as **type** string, so no joy there. ... I think, be covered by the new **data type** of INT64 (?) in PHP6). ... @**return** array Returns modified active record array with cast properties ...  
codeigniter.com/forums/viewthread/110393/ - 55k - [Cached](#) - [Similar pages](#)

4. [#ZF-1750] Make Db adapters **return** consistent **datatype** from ...

Most adapters **return** a string, even though you might expect the value of an auto-generated value would be an integer. The **datatype** is string because the ...  
framework.zend.com/issues/browse/ZF-1750 - 38k - [Cached](#) - [Similar pages](#)

5. REAL Software Forums • View topic - Empty Value of TEXT-**Datatype** ...

7 posts - 2 authors - Last post: Jan 21  
... **return** empty values in the RecordSet (for Fields with **Data Type** 'TEXT'), .... I don't get the content of the TEXT-Field here: SELECT **id**, ...  
forums.realsoftware.com/viewtopic.php?f=3&t=24927 - 23k - [Cached](#) - [Similar pages](#)

6. Oracle: PL/SQL Function **returning** objects, scalar **data types**, sql ...

Is it possible for a PL/SQL function to **return** a user-defined **data type** (i.e. ...  
REFSEQNO%**TYPE**) **return** TNode as TNode node; begin node.**id** := aRefSeqNo; ...  
en.allexperts.com/q/Oracle-1451/PL-SQL-Function-returning.htm - 18k

- [Cached](#) - [Similar pages](#)

## 7. [PDF] Re: How to **return** a user-defined **data type** object from a webservice?

File Format: PDF/Adobe Acrobat - [View as HTML](#)

"Id"). { foreach (PropertyInfo toField in. toRecord.GetType().GetProperties()) ... to specify a particular **data type** from a particular platform. ...

[www.tech-archive.net/pdf/Archive/DotNet/microsoft.public.dotnet.framework.webservices/2008-03/msg00018.pdf](http://www.tech-archive.net/pdf/Archive/DotNet/microsoft.public.dotnet.framework.webservices/2008-03/msg00018.pdf) - [Similar pages](#)

[Similar pages](#)

## 8. **Erlang data types** (Lesson 2) » article » Federico Feroldi's blog

So, let's take a brief look on Erlang's **data types** in this article. ... pass funs to as

parameter to function calls and **return** funs as function results: ... **ID**, **post\_title**,

**post\_name**, **post\_status**, **post\_date**, **CAST(meta\_value AS UNSIGNED)** ...

[www.pixzone.com/blog/220/erlang-data-types-lesson-2/](http://www.pixzone.com/blog/220/erlang-data-types-lesson-2/) - 21k - [Cached](#) - [Similar pages](#)

## 9. [Development/Tutorials/Akonadi/SerializerPlugin](#) - KDE TechBase

To use your own **data type** with KDE's API for Akonadi, you will need three things: ...

<history> <header> <local id="contactId1" /> <remote id="contactId2" /> </header> ....

Item::FullPayload ) **return** false; History history; if ( ! ...

[techbase.kde.org/Development/Tutorials/Akonadi/SerializerPlugin](http://techbase.kde.org/Development/Tutorials/Akonadi/SerializerPlugin) - 82k

- [Cached](#) - [Similar pages](#)

## 10. [Design Patterns as Higher-Order Datatype](#)-Generic Programs ...

The necessary features are higher-order and **datatype**-generic constructs; ...

implement subroutines by pushing arguments and **return** address onto the stack. ....

b=a) def fold(fb)(f :s{**type** a=Fix.this.a; **type** b=fb=>fb) : fb = f(bimap(**id**, ...

[lambda-the-ultimate.org/node/1360](http://lambda-the-ultimate.org/node/1360) - 37k - [Cached](#) - [Similar pages](#)

Tip: These results **do not include** the word "identify". [Show results that include "identify"](#).

◀  ▶  
[Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#) [Next](#)

returning id of data type to identify data type

[Search](#)

[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) - [Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)